

CE

COMBINED EC-, PH- AND TEMPERATURE METER WITH AUTOMATIC CALIBRATION MODEL EPH-119



This EC/pH/°C-meter has standard features like; automatic temperature compensation and automatic calibration. Is supplied complete in a rugged carrying case included accessories for water- and soil samples.

Technical specifications:

Manufacturer	: Nieuwkoop BV Aalsmeer Holland
Housing/operation	: ABS/ press button
Range pH/ EC/ Temp.	: 0-14,00pH/ 0-19,99mS/ 0-65,0°C
Accuracy/deviation	: ± 0,01pH/ ± 0,01mS/ ± 0,1 °C
Resolution	: 0,01 digit LCD
Temperature comp.	: Automatic for EC and pH.
Calibration	: Automatic with recognition of calibration liquids
Electrode pH	: Combined/epoxy, 100 cm cable with BNC connector
Electrode EC	: Epoxy with Pt-1000 temperature element
Power supply	: 1 x battery 9V 6F22
Consumption	: ± 300 hrs
Size/weight	: 320 x 290 x 120mm/ 2 kg
Options	: RS-232 output on request
Accessories	: Carrying case, sample cup, syringe, cleaning bottle, distilled-water, calibration liquids (pH-4, pH-7 and EC), storage liquid and a user manual.
Warranty	: 1 year (not on pH-electrode)



www.intekoagro.by

Your supplier: